

# 3M™ Rinse-Clean Coating RC-1000

3M™ Rinse-Clean Coating RC-1000 is an aqueous-based solution that forms a very thin, transparent coating over exterior surfaces such as painted walls, building claddings & panels, and outdoor graphic films. The hydrophilic nature of the coating allows simple water rinsing away of dust, soils and sludge from the surface with minimal residual surface staining.

## Features

- Improves dust repellence of surface
- Weather resistant
- Durable performance up to 2 years\*
- Easy to apply
- Green product

*\*Based in internal testing done on cladding*



## Dust repellence test

### Before test



Coated with  
RC-1000

Without  
coating

### After test



Coated with  
RC-1000

Without  
coating

## Product information

|                    |                                                   |
|--------------------|---------------------------------------------------|
| Packaging          | Carton                                            |
| Per Carton         | 4 × 4L Bottles                                    |
| Appearance         | Translucent liquid                                |
| Coverage           | 30m <sup>2</sup> /litre in a single-pass coat     |
| Shelf-life         | 12 months from date of manufacture                |
| Storage conditions | Away from sunlight, in a cool dry place (20-30°C) |
| Ordering SKU       | XT005599862                                       |



## Application Instructions

- A. Clean Surface
  - Clean the surface with suitable cleaning agent
  - Remove any obvious and visible surface contaminants
  - Surfaces with previous coatings may require additional mechanical cleaning
  - Rinse off any residual detergent and contaminants with water
- B. Apply 3M™ Rinse-Clean Coating RC-1000
  - Wet application sponge/roller with 3M™ Rinse-Clean Coating RC-1000
  - Apply a single layer by working from bottom edge to top edge, left to right or vice versa.
  - If needed, excess coating can be captured in a drain pan.
  - If necessary, wipe off any drops along the edges or streaks on the face with a clean cloth.
  - If desired, repeat application to increase number of layers.
  - Not for use on glass. If excess liquid drips on or gets in contact with glass, wipe off immediately with clean wet cloth

*For specific surfaces and applications, consult 3M representative.*

## Surface compatibility check

Due to the differences in surface properties & environmental conditions, the user must evaluate and determine if the surface is compatible with 3M™ Rinse Clean Coating RC-1000 before proceeding for full-scale large area application. It is recommended to first apply on a small area, and monitor for a period of time.

The surface is assessed to be incompatible if one or more the following are observed after coating

- Surface does not wet uniformly with obvious bead formation
- Coating solution is absorbed into material
- Discoloration of surface
- Rusting of surface

## Recommended Removal Methods

### Cladding

1. Wet 3M™ Doodlebug™ White Cleansing Pad 8440, 3M™ White Scouring Pad 98, Scotch-Brite™ Power Pad 2000 or equivalent with water.
2. Apply moderate force with pad on desired removal area and work from left to right or vice versa.

### Painted Surface

1. Wet 3M™ Doodlebug™ Blue Pad 8242, 3M™ Doodlebug™ Hi Pro Pad 8550, Scotch-Brite™ Pad 7447 or equivalent with water.
2. Apply force with pad on desired removal area and work from left to right or vice versa.
3. Thin layer of paint will be removed during the removal process.

## Precautionary Information

Refer to Safety Data Sheet for health and safety information before using this product.

Notice to Purchaser: The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. Since conditions of product use are outside of our control and vary widely, the following is made in lieu of all express or implied warranties (including the warranties of merchantability or fitness for a particular purpose): Except where prohibited by law, 3M's only obligation and your only remedy, is replacement or, at 3M's option, refund of the original purchase price of product that is shown to have been defective when you received it. In no case will 3M be liable for any direct, indirect, special, incidental, or consequential damages (including, without limitation, lost profits, goodwill, and business opportunity) based on breach of warranty, condition or contract, negligence, strict tort, or any other legal or equitable theory.

3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability and safety information before using this product.